## **HellermannTyton**



Article Number: 170-03084

Description: Braided Sleeving, Split Wrap, .75" Dia, PET, Orange, 100 ft/ bulk reel

| Base Data                   |                                 |  |
|-----------------------------|---------------------------------|--|
|                             |                                 |  |
|                             | Local Order Number              | 170-03084  |
|                             | Туре                            | BSPSW343B  |
|                             | Color                           | Orange (OG)  |
|                             | Features and Benefits           | <ul> <li>Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.</li> <li>Unique construction retains shape and rigidity throughout unrolling.</li> <li>Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.</li> </ul> |
|                             | Quantity Per                    | box  |
|                             | Product Description             | A lateral split, semi-rigid and flame retardant braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.    |
|                             | Short Description               | Braided Sleeving, Split Wrap, .75" Dia, PET, Orange, 100 ft/ bulk reel   |
| Product<br>Dimensions       |                                 |  |
|                             | Length L (Imperial)             | 100.0ft  |
|                             | Length L (Metric)               | 30.48m   |
|                             | Reel Length (imperial)          | 100.0ft  |
|                             | Bundle Diameter Max. (Imperial) | 0.75"  |
|                             | Bundle Diameter Max. (Metric)   | 19.1mm   |
|                             | Nominal Diameter (Imperial)     | 3/4"   |
|                             | Nominal Diameter (Metric)       | 19.1mm   |
| Material and Specifications |                                 |  |
|                             | Material                        | Polyester (PET)  |
|                             | Material Shortcut               | PET  |
|                             | Flammability                    | UL 94 V0   |
|                             | Operating Temperature           | -94°F to +248°F (-70°C to +125°C)  |

## 170-03084

## HellermannTyton

| Material and<br>Specifications | ROHS Compliant                | Yes        |
|--------------------------------|-------------------------------|------------|
|                                | UL Recognized (US and Canada) | Yes        |
| Logistic and<br>Packaging      |                               |            |
|                                | Package Quantity (Imperial)   | 100ft      |
|                                | Package Quantity (Metric)     | 30.48m     |
|                                | Customs Number(Schedule B)    | 3926909987 |
|                                | Weight (imperial)             | 1.6lbs     |
|                                | Weight (Metric)               | 0.73kg     |